

EPOTEC RD 102

Description

EPOTEC RD 102 is the monoglycidyl ether of butyl alcohol. The primary use of RD 102 is as a reactive diluent for high viscosity epoxy resins. RD 102 is compatible at all concentrations and those resins and the blends can be cured with variety of epoxy hardeners. As with all monofunctional aliphatic epoxies, increasing level of RD 102 will increase pot life and modify cured properties.

Applications

- Flooring
- Potting and encapsulation
- General purpose adhesives

Typical properties

Property	Test method	Unit	Specification
Appearance	Visual	-	Clear liquid
Colour	ASTM D-1544 (89) TEC-AS-P-006	Gardner	Max. 0.2
Epoxy equivalent weight	DIN 16945/4.15B (89) TEC-AS-C-002	g/eq	140 - 165
Viscosity* @ 25°C	JIS K 7233 (86)	cPs	1.2 – 1.8

* Brookfield viscosity

Storage

EPOTEC RD 102 should be stored in dry condition in original sealed container. Under these conditions, it has a storage life of at least one year.

Handling

Please refer to MSDS for safe handling of EPOTEC RD 102.

Disclaimer

All recommendations for use of our products whether given by us in writing, verbally or to be implied from the results of tests carried out by us are based on the current state of our knowledge. Although, the information contained in this sheet is accurate, no liability can be accepted in respect of such information. We warrant only that our product will meet the designated specifications and make no other warranty either express or implied, including any warranty of merchantability or fitness for a particular purpose as the conditions of application are beyond our control.

For additional information:

ADITYA BIRLA CHEMICALS (EPOXY DIVISION)

16thFLOOR MAHATHUN PLAZA. 888/160-161 PLOENCHIT ROAD, BANGKOK 10330 THAILAND.

TEL: (662) 2535031-3, 2536882, FAX: (662) 2535030

Website: www.thaiepoxy.com, E-mail: epotec@thaiepoxy.com