

## EPOTEC YD 128S

### Description

EPOTEC YD 128S is an unmodified liquid epoxy resin reaction product of Bisphenol A and epichlorohydrin. It shows much better crystallization resistance compared for standard liquid resin. When it cured with appropriate hardner, it gives excellent mechanical, chemical and adhesion properties in cured state. Because of these properties it found uses in various applications.

### Applications

- High solid solvent free coatings
- Adhesives
- Civil engineering and construction industry
- Composites, fiber reinforced pipes

### Typical properties

Property	Test method	Unit	Specification
Appearance	Visual	-	Viscous liquid
Color	ASTM-D-1544 (89) TEC-AS-P-006	Gardner	Max. 1.0
Epoxy equivalent weight	DIN 16945/4.15B (89) TEC-AS-C-002	g/eq	210 - 225
Hydrolysable chlorine	ASTM D-1726 (87) TEC-AS-C-007	Wt%	1.85 -2.50
Viscosity* @ 25°C	JIS-K-7233 (86)	cPs	17,000 - 23,000

\* Brookfield viscosity

### Storage

EPOTEC YD 128S resin should be stored in original tightly closed container, in dry and warm conditions. Under these conditions, it has a storage life of at least one year.

### Handling

Please refer to MSDS for safe handling of EPOTEC YD 128S.

### Disclaimer

All recommendations for use of our products whether given by us in writing, verbally or to be implied from the results of tests carried out by us are based on the current state of our knowledge. Although, the information contained in this sheet is accurate, no liability can be accepted in respect of such information. We warrant only that our product will meet the designated specifications and make no other warranty either express or implied, including any warranty of merchantability or fitness for a particular purpose as the conditions of application are beyond our control.

### For additional information:

#### ADTIYA BIRLA CHEMICALS (EPOXY DIVISION)

16<sup>th</sup>FLOOR MAHATHUN PLAZA. 888/160-161 PLOENCHIT ROAD, BANGKOK 10330 THAILAND

TEL: (662) 2535031-3, 2536882, FAX: (662) 2535030

Website: [www.thaiepoxy.com](http://www.thaiepoxy.com), E-mail: [epotec@thaiepoxy.com](mailto:epotec@thaiepoxy.com)